

LEVEL-2

GPS Anti-Jamming Active Filter - The Time Firewall Subsystem

ELPROMA says
"Better Safe Than Sorry"



- Anti-jamming Active Filter
- Supports L1 1575,42 MHz
- Protects GPS L1 C/A Code
- Passthrough GLONASS
- No config - fully automatic
- Auto attack detection
- Holdover auto switch-on
- End of attack switch-off
- Redundant PWR-supply
- Built-in 2x GNSS Receiver
- Compatible to: NTS-5000
NTS-3000 NTS-4000

NTS-LEVEL-2 automatically recognizes and eliminates false GPS L1 C/A code send over 1575,42MHz frequency carrier. Simultaneously, it passthrough GLONASS 1598,06-1605,38MHz. It is dedicated anti-jamming active filter.

Device is a cyber-security class rack"19 (1U) mount device. It operates fully automatic (no setup configuration). It includes 2x build-in GNSS receivers LEVEL-1 100% compatible to NTS-antenna. NTS-LEVEL-2 provides clean filtered GPS output directly to ELPROMA NTS-family servers. Device introduces +/- 15ns error. The cable delay can be compensated and stored.



Technical Specification

2x GNSS built-in SAT receivers operating redundant

Receiver #1 => Jamming filter ON => supports GPS => ANT 1
 Receiver #2 => Jamming filter OFF => supports GNSS => ANT 2

GPS/GNSS Receiver Time Accuracy better than 20 ns
 Supporting antenna cable length compensation

Active filter supports GPS L1 1575,42MHz with C/A (Receiver #1)
 Active filter supports transparency for GLONASS R1 (Receiver #1)
 FURUNO GT-series w/ Multipath Mitigation (option Receiver #2)

(T)RAIM Support
 32-170* multi-channel
 700m [2300ft] UTP cat. 5 LEVEL-2 to LEVEL-3 or NTS-x000 dist.
 RS485 (std) or Fiber Optic* using FO-01 (extra option)

3x INPUT Antenna (SMA) RF GPS L1 1575,42MHz w/ C/A code

ANT A'	(primary)	GPS receiver #1
ANT A''	(secondary)	GPS receiver #1
ANT B	(auxiliary)	GPS receiver #2

2x OUTPUT Antenna (RJ45) serial RS485 ToD+1PPS

ANT 1 => NTS-x000 NMEA183 + 1PPS (FILTERED)
 ANT 2 => NTS-x000 NMEA183 + 1PPS (UNFILETERD)

2x Power Supply (redundant)

110-230 VAC (1A) 50-60Hz & 120-370 VDC (1A)
 20-70 VDC (2A) /extra option/

Size: 484 x3 00 x 44,4 mm (rack'19 1U)
 Operating temp. : 0°C to +60°C (server)
 -55°C to +80°C (antenna)

India sales & support partner
www.kpmttek.com
sales@kpmttek.com
 +91 124 4001088

e-mail: info@elpromatime.com

 **ELPROMA**
www.elpromatime.com